

## German standard multi-outlet extensions with cord (continued)



6 946 21



6 946 26





6 946 36

Pack	Cat.Nos	Multi-outlet extensions for comfort	Pack	Cat.Nos	Standard multi-outlet extensions
5 5 5 5 5	6 946 26 6 946 36 6 946 22 6 946 27	On/off switch with a light indicator, can be operated by foot or by hand Socket with child protection shutters tested to withstand 10000 operations Orientable socket outlets Maximum space between 2 sockets to connect transfos, chargers, etc. Supplied with self-gripping tie for grouping the cords of the connected devices Direct wall-mounting possibilities (with screws) Cable management possible around the wall-mounting fixtures With power supply cord 1.5 m (3G 1 mm²) or 3 m (3G 1.5 mm²) 16 A max. power 3500 W at 230 V 1.5 m cord 4 x 2P+½ - 1.5 m cord 4 x 2P+½ - 1.5 m cord 3 x 2P+½ - 3 m cord 4 x 2P+½ - 3 m cord 6 x 2P+½ - 3 m cord	10 10 10 10 10 10 10 10	6 950 06 6 950 16 6 950 02 6 950 07 6 950 17 6 950 03 6 950 08	To connect several devices equipped with plugs with or without earth: appliances class I (simple insulation) or class II (double insulation), lamps, PC, TV, stereo, etc. Ultra-flat: can be slid underneath furniture Wall-mounting possibilities with the packaging accessory $90^\circ$ socket for connecting a transformer without blocking another socket Power supply cord 1.5 m (3G 1 mm²) or 3 m (3G 1.5 mm²) or 5 m (3G 1.5 mm²) 16 A max. power 3 500 W at 230 V